

CLAMPING SET YT



Type	Screw thread	T - slot [mm]	Quantity	Weight [kg]
YT-0202	M10	12	58	5,8
YT-0204	M12	14	58	8,1
YT-0206	M14	16	58	9,0
YT-0208	M16	18	58	13,5
YT-0210	M18	20	58	18,5
YT-0212	M20	22	58	24,0

Properties and application:

- Clamping set for use in milling, drilling and similar works.
- Pieces are hardened, tempered and oxidized.
- Set includes:
 - T-slot nut: 6 pcs
 - Flanged nut: 6 pcs
 - Extended nut: 4 pcs
 - Serrated support: 12 pcs
 - Serrated holding clamp: 6 pcs
 - Double ended screw: 24 pcs

PARALLEL SETS PF



Properties and application:

- Made of high-quality alloy steel
- Hardness: 55 - 62 HRC
- Tolerance of a single pair: 0,01 mm
- Used in pairs to set elements in vices above the thrust plane

Type	Length [mm]	Thickness [mm]	Height [mm]	Weight [kg]
PF 80/4 - 14/50x14 PB150-3	80±0,2	4±0,2	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40, 45, 50	3,7
PF 100/4 - 10/42x9 PB151-1	100±0,2	4±0,2	10, 14, 18, 22, 26, 30, 34, 38, 42	2,3
PF 120/8 - 12/38x8 PB156-1	120±0,2	8±0,2	12, 17, 22, 25, 28, 32, 36, 38	4,6
PF 120/10 - 14/40x12 PB155-1	120±0,2	10±0,2	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40	7,8
PF 150/4,6 - 20/30x6 PB157-1	150±0,2	4,6±0,2	20, 22, 24, 26, 28, 30	2,3
PF 150/4,6 - 32/44x6 PB157-2	150±0,2	4,6±0,2	32, 34, 36, 38, 40, 44	3,5
PF 150/8 - 16/50x18 PB154-1	150±0,2	8±0,2	16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50	14,3
PF 150/8 - 17/51x18 PB154-2	150±0,2	8±0,2	17, 19, 21, 23, 25, 27, 29, 31, 33, 35, 37, 39, 41, 43, 45, 47, 49, 51	13,8
PF 150/8 - 14/50x14 PB150-2	150±0,2	8±0,2	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40, 45, 50	9,9
PF 150/8,5 - 14/44x9 PB151-3	150±0,2	8,5±0,2	14, 16, 20, 24, 30, 32, 36, 40, 44	6,7
PF 150/10 - 14/50x14 PB150-1	150±0,2	10±0,2	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40, 45, 50	11,9
PF 150/10 - 14/40x12 PB155-2	150±0,2	10±0,2	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40	8,3
PF 160/4 - 10/42x9 PB151-2	160±0,2	4±0,2	10, 14, 18, 22, 26, 30, 34, 38, 42	3,5
PF 160/8 - 12/38x8 PB156-2	160±0,2	8±0,2	12, 17, 22, 25, 28, 32, 36, 38	5,5
PF 200/8 - 17/43x8 PB156-3	200±0,2	8±0,2	17, 22, 25, 28, 32, 36, 38, 43	7,7
PF 200/10 - 14/50x14 PB150-4	200±0,2	10±0,2	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40, 45, 50	14,7