


▼B011010-B011410

LIGHT-DUTY LIVE CENTER




Hardened to 61-65 Rockwell.
Three precise and high quality bearings.



Order NO.	Model	d mm/in.	D mm/in.	A mm/in.	B mm/in.	L mm/in.	TIR mm/in.	N.W. kg/lbs.	Max. R.P.M	Price
B011010	BZZ-MT1	18 0.71	38 1.5	24 0.94	56 2.2	119 4.69	0.008 0.0003	0.7 1.55	3000	
B011110	BZZ-MT2	21 0.83	48 1.89	30 1.18	69 2.72	147 5.79	0.008 0.0003	0.8 1.77	3000	
B011210	BZZ-MT3	26 1.02	54 2.13	34 1.34	86 3.39	180 7.09	0.008 0.0003	2.2 4.86	2500	
B011310	BZZ-MT4	32 1.26	63 2.48	44 1.73	108 4.25	224.5 8.84	0.008 0.0003	3.4 7.52	2000	
B011410	BZZ-MT5	42 1.65	83 3.27	54 2.126	136 5.35	267.5 10.53	0.008 0.0003	5.78 12.78	2000	

▼B021010-B021310

MEDIUM LIVE CENTER




• HRC:58±2.

- Standard design structure, top diameter increase.
- CNC technology processing.
- Use special bearings, radial and axial force.
- Speed 2000r/m.
- HRC:58±2.

Order NO.	Model	A mm/in.	B mm/in.	C mm/in.	D mm/in.	D1 mm/in.	d mm/in.	L mm/in.	TIR mm/in.	θ	N.W. kg/lbs.	Price
B021010	BZ-MT.3B	32 1.26	53 2.09	86 3.39	53 2.09	23.5 0.93	-	170 6.69	0.008 0.0003	60°	1.28 2.8	
B021110	BZ-MT.4B	39 1.54	65 2.56	108 4.25	63 2.48	30 1.18	-	212 8.35	0.008 0.0003	60°	2.2 4.9	
B021210	BZ-MT.5B	53 2.09	83 3.27	136 5.35	78 3.07	44 1.73	-	260 10.2	0.008 0.0003	60°	4.33 9.6	
B021310	BZ-MT.6B	80 3.15	110 4.33	189 7.44	128 5.04	70 2.76	-	379 14.9	0.008 0.0003	60°	14.2 31.4	

▼B031010-B031310

MEDIUM LIVE CENTER



• HRC:58±2.

- Standard design structure, external rotation dustproof and waterproof.
- CNC technology processing.
- Use special bearings, radial and axial force.
- The unique dustproof, waterproof design
- Speed 2000r/m.
- HRC:58±2.

Order NO.	Model	A mm/in.	B mm/in.	C mm/in.	D mm/in.	D1 mm/in.	L mm/in.	TIR mm/in.	θ	N.W. kg/lbs.	Price
B031010	BZ-MT.3D	36 1.4	65 2.6	86 3.4	53.5 2.1	26 1	192 7.6	0.008 0.0003	60°	1.28 2.82	
B031110	BZ-MT.4D	40 1.57	74.5 2.93	108 4.25	63 2.48	28 1.1	215 8.46	0.008 0.0003	60°	2.2 4.862	
B031210	BZ-MT.5D	54 2.13	93.5 3.68	136 5.35	76 2.99	36.5 1.44	272 10.7	0.008 0.0003	60°	4.33 9.57	
B031310	BZ-MT.6D	80 3.15	110 4.33	189 7.44	128 5.04	70 2.76	379 14.9	0.008 0.0003	60°	14.2 31.38	